



TS 108

Operating Limits

Pressure: $\leq 1\text{MPa}$

Speed: $\leq 10\text{ m/s}$

Temperature: $-30^{\circ}\text{C} \sim +200^{\circ}\text{C}$

- Rotary Ring(Plastic Carbon/Carbon/SiC/TC)
- Stationary Ring(Ceramic/SiC/TC)
- Secondary Seal(NBR/EPDM/VITON)
- Spring & Other Parts(SUS304/SUS316)

Model	d ₁ (mm)	d ₃	d ₇	l ₁	l ₃
TS108-9	9	20.0	21	20	5.0
TS108-10	10	20.0	21	20	5.0
TS108-11	11	22.0	23	20	5.0
TS108-12	12	22.0	23	20	5.0
TS108-14	14	24.5	25	25	5.2
TS108-15	15	26.5	27	25	5.2
TS108-16	16	26.5	27	25	5.2
TS108-17	17	32.0	33	25	5.2
TS108-18	18	32.0	33	25	5.2
TS108-19	19	34.0	35	25	7.5

Model	d ₁ (mm)	d ₃	d ₇	l ₁	l ₃
TS108-20	20	34.0	35	25	7.5
TS108-22	22	36.0	37	28	7.5
TS108-25	25	39.0	40	32	8.0
TS108-28	28	42.0	43	35	8.0
TS108-30	30	44.0	45	35	8.0
TS108-35	35	49.0	50	37	8.0
TS108-40	40	56.0	58	40	8.7
TS108-45	45	61.0	63	40	9.0
TS108-50	50	67.0	70	45	9.0
TS108-55	55	72.0	75	45	10.5