



TS CG

Operating Limits

Pressure: $\leq 1.2\text{MPa}$

Speed: $\leq 10\text{ m/s}$

Temperature: $-30^\circ\text{C} \sim +200^\circ\text{C}$

Replace John Crane type 2100 with "BO" seat ,
and "G60" seat also can be provided

- Rotary Ring(Carbon/SiC/TC)
- Stationary Ring(Ceramic/SiC/TC)
- Secondary Seal(NBR/EPDM/VITON)
- Spring & Other Parts(SUS304/SUS316)

Model	d_1 (mm)	d_3	d_7	l_1	l_3
TSCG-16	16	26	27	15	12.0
TSCG-18	18	32	33	20	13.5
TSCG-20	20	34	35	20	13.5
TSCG-22	22	36	37	20	13.5
TSCG-24	24	38	39	20	13.5
TSCG-25	25	39	40	20	13.0
TSCG-28	28	42	43	26	12.5
TSCG-30	30	44	45	26	12.0
TSCG-32	32	46	48	26	12.0
TSCG-33	33	47	48	26	12.0
TSCG-35	35	49	50	26	12.0
TSCG-38	38	54	56	30	13.0

Model	d_1 (mm)	d_3	d_7	l_1	l_3
TSCG-40	40	56	58	30	13.0
TSCG-43	43	59	61	30	13.0
TSCG-45	45	61	63	30	13.0
TSCG-48	48	64	66	30	13.0
TSCG-50	50	66	70	30	13.5
TSCG-53	53	69	73	30	13.5
TSCG-55	55	71	75	30	13.5
TSCG-60	60	80	80	33	13.5
TSCG-65	65	85	85	33	13.5
TSCG-70	70	90	92	33	14.5
TSCG-75	75	99	97	40	14.5