



Replace John Crane Type 2 with 'cup' seat (US Standard), and O-Ring seat also can be provided.

TS T2

Operating Limits

Pressure: $\leq 2.8\text{MPa}$

Speed: $\leq 13\text{ m/s}$

Temperature: $-30^{\circ}\text{C} \sim +200^{\circ}\text{C}$

- Rotary Ring(Carbon/SiC/TC)
- Stationary Ring(Ceramic/SiC/TC)
- Secondary Seal(NBR/EPDM/VITON)
- Spring & Other Parts(SUS304/SUS316)

Model	d ₁ (inches)	d ₃	d ₇	l ₁	l ₃
T2-1"	25.400	46.00	41.275	36.50	11.10
T2-1 1/8"	28.575	49.20	44.450	38.10	11.10
T2-1 1/4"	31.750	52.40	47.625	38.10	11.10
T2-1 3/8"	34.925	57.20	50.800	39.70	11.10
T2-1 1/2"	38.100	60.30	53.975	39.70	11.10
T2-1 5/8"	41.275	69.00	60.325	47.63	12.70
T2-1 3/4"	44.450	69.90	63.500	47.63	12.70
T2-1 7/8"	47.625	73.00	66.675	50.80	12.70
T2-2"	50.800	76.20	69.850	50.80	12.70
T2-2 1/8"	53.975	82.50	76.200	57.15	14.30
T2-2 1/4"	57.150	85.70	79.375	57.15	14.30
T2-2 3/8"	60.325	88.90	82.550	60.30	14.30
T2-2 1/2"	63.500	94.00	85.725	60.30	14.30
T2-3"	76.200	107.95	98.425	68.28	15.90
T2-4"	101.600	141.28	123.830	78.57	19.84